



Cold Heading Wire



Technical Specs

Form:	Coils (loose of layer wound) Conical coils Spiders Z2 and Z3 coils
Packaging:	On pallets With a cardboard centre On a wooden beam With lifting eyes Wrapped in plastic Wrapped in polycrêpe paper
Dimension range :	Dimension range 1.25-11.00 mm.
Weigth per unit	250kg - 2.000kg
Treatments	Pickled Annealed Drawn
In the following combinations:	+U+C

Address

Klein Terbankstraat 65
B-3150 Tildonk

TREBOS Duferco N.V.

VAT BE 0836 702 796
IBAN BE42 6430 0483 8054
SWIFT BMPBBEBB

Contact

+32 16 61 81 81
+32 16 60 62 41
commercial@trebos.com

Certificates

ISO 9001:2008
ISO 14001:2004



+AC+C

+A+C+AC

+U+C+AC+LC

+A+C+AC+LC

Surface:

Phosphated

soap drawn

copper coated

finally annealed

Steelgrade:

C4C- C8C- C10C - C15C - C20C- C15E2C -C17E2C - C20E2C- C35EC- C45EC -
17B2 - 23B2 - 33B2- 38B2 - 17MnB5 - 19MnB4(Cr) - 20MnB4 - 23MnB4 - 30MnB4
- 27CrB4 – 42CrMo4 Other analysis on request

**European
standard:**

Grade DIN EN 10263 part 2-4, DIN EN 10267



Address

Klein Terbankstraat 65
B-3150 Tildonk

TREBOS Duferco N.V.

VAT BE 0836 702 796
IBAN BE42 6430 0483 8054
SWIFT BMPBBEBB

Contact

+32 16 61 81 81
+32 16 60 62 41
commercial@trebos.com

Certificates

ISO 9001:2008
ISO 14001:2004